β_3

TW8a

8" Two Way Full Range Active Speaker

DESCRIPTION

Portable and installed active loudspeakers used in applications including sound reinforcement in Front of House and Foldback applications in house of worship, events, clubs, rehearsal etc. Both active and passive version deliver extraordinary performance at unmatched value.



FEATURES

- High output SPL and sensitivity
- Built-in high power amplifier module with DSP
- Master volume control
- XLR input and output connectors
- Smart sound quality adjustment
- Integrated pole mount adaptor at bottom
- Portable system (stand), or permanent installation (wall, ceiling, under balcony)
- Suitable for use as a main system with or without sub speaker augmentation
- Powder coated protective grill
- Durable Polyurethane textured base paint



TECHNICAL SPECIFICATIONS

Acoustical specifications	Frequency Response(-3db):	85Hz-18kHz
	Max SPL @ 1m:	112dB/118dB(PEAK)
	Dispersion (H x V):	130° × 140°
Transducers	Compression driver:	1 x 1" HF
	Woofer:	1 x 8" LF
Input/Output section	Input signal:	Balanced $20k\Omega$, Unbalanced $10k\Omega$
	Input Connectors:	XL/TRS,RCA,Mixed male output
Power section	Total Power:	450W(RMS); 900W(MUSIC); 1800W(PEAK);
	Nominal Impedance (Ohm):	8Ω
	Voltage range:	AC 220V-240V~, 50/60Hz (or AC 110V-120V~, 50/60Hz)
Physical specifications	Color:	Black
Size	Dimension (W x D x H):	225 x 270 x 408mm / (8.9 x 10.6 x 16.1in)
	Package Dimensions (W x D x H):	345 x 305 x 495mm / (13.6 x 12 x 19.5in)
Weight	Net Weight:	10 kg / 22 lb
	Gross Weight:	11 kg / 24.3 lb