

ΣB115D

15" Bandpass LF Speaker

DESCRIPTION

The Beta Three® ΣB Series Sub speakers utilise high power low frequency drivers with structurally solid enclosures with bandpass configurations. The ΣB Series Sub speakers deliver extended low frequency bandwidth with excellent punch. Suitable for Performing Arts, Auditoriums, Clubs, Houses of Worship, Entertainment Venues and Indoor Sports Facilities.



FEATURES

- High sensitivity and SPL
- 1 x 15" high power low frequency transducer
- Six order bandpass configuration
- Speakon input connectors
- Computer aided design to optimise frequency and phase response
- Stacking locators
- Suitable for use with any full range or mid/high speaker cabinets for extended low frequency, high quality music reproduction
- Integral 35mm pole receptacle for mounting full range or mid/high speaker cabinets
- Durable Polyurethane textured base paint

TECHNICAL SPECIFICATIONS

Acoustical specifications	Frequency Response(-3db):	50Hz-150Hz
	Max SPL @ 1m:	125dB/131dB(PEAK)
Transducers	Woofer:	1 x 15" LF
Input/Output section	Input Connectors:	2 x NL4
	Sensitivity (1W @ 1m):	99dB
Power section	Total Power:	450W(RMS); 900W(MUSIC); 1800W(PEAK);
	Nominal Impedance (Ohm):	8Ω
Physical specifications	Color:	Black
Size	Dimension (W x D x H):	600 x 500 x 460mm / (23.6 x 19.7 x 18.1in)
	Package Dimensions (W x D x H):	720 x 610 x 590mm / (28.3 x 24 x 23.2in)
Weight	Net Weight:	29 kg / 63.9 lb
	Gross Weight:	33.4 kg / 73.6 lb