

# BA1602

Public Address Amplifier

## DESCRIPTION

BA1602 600W public address amplifier is designed and engineered to suit public address installations where continuous high power is required. This versatile mixer amplifier can be used in a wide variety of public address applications.



## FEATURES

- 2 x balanced XLR or 6.5mm line level inputs
- Selectable voltage binding post outputs
- Front panel volume controls for each channel
- LED signal, peak and power indicators
- Voltage outputs 50V, 70V, 100V - bridge mode 100V, 140V, 200V
- Protection for short circuit, over load, over heat
- Variable speed fans

## TECHNICAL SPECIFICATIONS

---

Rated Power	2 x 625W (RMS) Dual Channel, 1250W (Bridged)
THD (@1kHz)	<0.5% (Normal working condition)
Amplifier Type	
S/N Ratio	100dB
Damping Factor	
Frequency Response (+0/-0.25dB)	50Hz-16kHz
Input Sensitivity	1V
Input Impedance	20kΩ Balanced, 10kΩ Unbalanced
Input connector	XLR/6.5mm socket
Output Connector	Crew Terminal
Power Supply	220V/230V 50/60H, 600VA
Cooling	
Dimensions (W x D x H)	483mm (19") x 376mm (14.8") x 88mm (3.5")
Packing Dimension (W x D x H)	
Net Weight	22kg (48.5lb)
Gross Weight	23kg (50.7lb)

---