

QS400

4" Public Address Speaker

DESCRIPTION

QS400 is a 4" two way full range speaker system with wide dispersion. Its sound is nature and clear while the cabinet is handy, compact and the appearance is elegant and fashionable. It's applicable in small performing stages, KTV, background music, etc.



FEATURES

- Two 1" dome tweeter
- 4" paper cone low frequency driver
- High intensity injection moulded cabinet
- Dispersion 90° x 90°
- Frequency response 120Hz-20kHz(-3dB)
- Sensitivity 88dB, Max SPL 108dB(peak)
- Constant max power 25W
- 2xM5 hanging point
- Customizable grill and cabinet color
- Appearance elegant and fashionable
- Built-in mounting bracket

TECHNICAL SPECIFICATIONS

Acoustical specifications	Frequency Response(-3db):	120Hz-20kHz
	Max SPL @ 1m:	102dB/108dB(PEAK)
	Dispersion (H x V):	90° x 90°
Transducers	Compression driver:	2 x 1" HF
	Woofer:	1 x 4" LF
Input/Output section	Input Connectors:	Wire clamp
	Sensitivity (1W @ 1m):	88dB
Processor section	Crossover frequencies:	6.3kHz
Power section	Total Power:	25W(RMS); 50W(MUSIC); 100W(PEAK);
	Nominal Impedance (Ohm):	8Ω
	Voltage range:	120V/100V/70V
Physical specifications	Cabinet/Case Material:	Polypropylene injection moulding
	Hardware:	2 x M5 Bracket lifting point
	Grille:	Cabinet Exterior with/without polyurethane spraying treatment (depends on colors)Grill with cloth
	Color:	Black
Size	Dimension (W x D x H):	238 x 135 x 142mm / (9.4 x 5.3 x 5.6in)
	Package Dimensions (W x D x H):	372 x 192 x 310mm / (14.6 x 7.6 x 12.2in)
Weight	Net Weight:	1.7 kg / 3.7 lb
	Gross Weight:	4 kg / 8.8 lb