

TH215/64/96

15" 2-Way full Range Speaker

DESCRIPTION

TH Series is designed for permanent installation within medium to large Theatre venue sound reinforcement system applications, the outstanding mid/high performance ensures clean, clear and natural sound throughout the listening environment, even at high SPL.



FEATURES

- High SPL and High Sensitivity low frequency system
- 1x15" high power subwoofer
- High strength cabinet structure
- suitable for use as a main system with TH306/64 or TH306/93
- Computer aided design to optimize frequency and phase response
- Powder coated grill
- Durable Polyurethane textured base paint
- suitable for theatre ,television studio, multi-functional room and performance tudio



TECHNICAL SPECIFICATIONS

Acoustical specifications	Frequency Response(-3db):	40Hz-19kHz
	Max SPL @ 1m:	Passive: 116dB/122dB(PEAK); Bi-amp: MF: 116dB/122dB(PEAK), HF: 114dB/120dB(PEAK)
	Dispersion (H x V):	TH215H/64: 60°x 40°; TH215H/96: 90°x 60°
Transducers	Compression driver:	1 x 44mm HF
	Woofer:	1 x 15" LF
Input/Output section	Input Connectors:	1 x NL8, 8-way binding post
	Sensitivity (1W @ 1m):	Passive: 98dB; Bi-amp: LF: 97dB; HF: 107dB
Processor section	Crossover frequencies:	1.5kHz-2.5kHz
Power section	Total Power:	350W(RMS); 700W(MUSIC); 1400W(PEAK);
	Nominal Impedance (Ohm):	8Ω
Physical specifications	Hardware:	19 x M10
	Color:	Black
Size	Dimension (W x D x H):	440 x 470 x 680mm / (17.3 x 18.5 x 26.8in)
	Package Dimensions (W x D x H):	580 x 550 x 800mm / (22.8 x 21.7 x 31.5in)
Weight	Net Weight:	28 kg / 61.7 lb
	Gross Weight:	31.5 kg / 69.4 lb