

GS115Ba

15" Active Subwoofer

DESCRIPTION



FEATURES

- Compact cabinet with big dynamic LF performance.
- Specially designed amplifier module for KTV performance.
- Built-in circuit for loudspeaker phase adjustment and transient distortion.
- Computer aided design to optimize frequency and phase response.
- One 12" Low frequency Driver.
- Band pass design, High intensity enhanced cabinet construction.
- 300W amplifier Module.
- Suitable for enhanced low frequency venues.

TECHNICAL SPECIFICATIONS

Acoustical specifications	Frequency Response(-3db):	40Hz-150Hz
	Max SPL @ 1m:	123dB
Transducers	Woofers:	1 x 15" LF
Input/Output section	Input signal:	Balanced 20k Ω , Unbalanced 10k Ω
	Input Connectors:	XLR
Power section	Total Power:	500W(RMS); 1000W(MUSIC); 2000W(PEAK);
	Nominal Impedance (Ohm):	8 Ω
	Voltage range:	AC 220V-240V~, 50/60Hz (or AC 110V-120V~, 50/60Hz)
Physical specifications	Cabinet/Case Material:	15mm, 11 layer Plywood
	Handles:	2 x Wooden handles
	Grille:	Black polyurethane for the cabinet and Black power coating for the grill
	Color:	Black
Size	Dimension (W x D x H):	500 x 450 x 468mm / (19.7 x 17.7 x 18.4in)
	Package Dimensions (W x D x H):	610 x 570 x 580mm / (24 x 22.4 x 22.8in)
Weight	Net Weight:	36.5 kg / 80.5 lb
	Gross Weight:	39 kg / 86 lb