

AK3200

Stereo Mixing Karaoke Amplifier

DESCRIPTION



FEATURES

- Refraining the whistle
- Automatic selection for signal sources
- Available for KTV Room
- Available for connecting 3 groups speaker simultaneously
- Built-in vocal embellishment circuit, make the sound rich & natural
- Built-in strong refrigerant fan for ventilation to meet for a long period of time working.

TECHNICAL SPECIFICATIONS

Rated Power (RMS)	200W+200W+200W(1KHz,80hm)
THD (@1kHz)	0.02% (1KHz,100W,80hm)
Frequency Response(-3dB)	20Hz-20kHz±2dB
Input Sensitivity/Impedance	MIC: 20mV/2kΩ
	Line: 200mV/10kΩ
	Video: 1Vp-p/750hm
Pitch Control	Music: LF(100Hz) ±10dB
	HF(10KHz) ±10dB
	MIC: LF(100Hz) ±10dB
	HF(10kHz) ±10dB
Effect Type	Echo
Pitch change control	±4
Output Impedance	4-16Ω
Recommendatory Impedance	8Ω
Power Supply	~110V/~220V,50Hz
Power Consumption	□1000W
AC output socket	One group with switch: 200W Two groups without switch: 300W
Static Power Consumption	30W
Net Weight (1 pc)	12.5kg
Gross Weight (1 pc)	14.0kg
Dimension(W×D×H)	505x435x200(mm)