

CS2315A

Dual 15" 3-Way Full Range Cinema Speaker

DESCRIPTION

This is a two cabinet system consisting of a two-way mid/high horn loudspeaker and a separate subwoofer loudspeaker cabinet. This Series specifically designed and engineered to meet requirements within Digital Cinema installations where high quality music and vocal reproduction is essential.



FEATURES

- Four transducers three way full range
- System type: three-frequency single drive or dual drive loudspeaker
- High frequency harmonic attenuation patented technology wooden horn
- High frequency no vertical pointing Angle adjustable
- Adjusting range + 20 ° to 30 °
- Bass with ultra-high perforation rate steel mesh protection, against mechanical damage and insect damage
- Three-frequency dual channel power amplifier drive
- Suitable for big/mid cinema audio system



TECHNICAL SPECIFICATIONS

Acoustical specifications	Frequency Response(-3db):	LF: 40Hz-550Hz; HF/HF: 400Hz-15kHz
	Max SPL @ 1m:	126dB/132dB(PEAK)
	Dispersion (H x V):	90° x 40°
Transducers	Compression driver:	1 x 75mm voice coil HF driver
	Midrange:	1 x 10" MF
	Woofer:	2 x 15" LF
Input/Output section	Input Connectors:	Spring clip
	Sensitivity (1W @ 1m):	LF: 100dB; MF/HF: 105dB
Processor section	Crossover frequencies:	LF/MF: 400Hz; MF/HF: 1.5kHz
Power section	Total Power:	LF: 900W; MF/HF: 300W(RMS);
	Nominal Impedance (Ohm):	LF: 4Ω; MF/HF: 8Ω
Physical specifications	Color:	Black
Size	Dimension (W x D x H):	LF: 700×1000×600mm; MF/HF: 700×731×508mm
	Package Dimensions (W x D x H):	LF: 810 x 660 x 1120mm; MF/HF: 855 x 816 x 638mm
Weight	Net Weight:	98.5 kg / 217.2 lb
	Gross Weight:	109 kg / 240.3 lb