## VX15a 15" Two-Way Full-Range Active Speaker



## DESCRIPTION

The VX series of multifunctional speaker system is designed for various applications requiring sound solutions of high durability and portability. The cabinet is made of Polypropylene material, with a special medium that is specially added to improve sound quality. Equipped with excellent wear-resistance, along with outstanding sound quality performance. VX15a is a two-way full-range active speaker composed of a 15" LF woofer and a 1" HF compression driver with Titanium diaphragm.Its characteristics include big dynamic, high sensitivity,clear MF and HF with powerful LF. VX15a adopts the integrative design of the horn and cabinet, with two rigging points at the top, one at the back, and there is mounting hole at the bottom of the cabinet. Each Handle at back of upper and sides of cabinet. Standard rigging design ensures installation and ourdoor portability.



## **FEATURES**

- 1000 watts (peak) 500 watts (program)
- Superior DSP processing with component protection
- 15-inch woofers with 2.5-inch voice coils
- 1-inch HF compression drivers
- 80° x 120° HF dispersion
- Dual purpose full-range and wedge monitor speaker
- Ultra-clear reproduction throughout the whole audio bandwidth
- Lightweight and high efficiency bi-amped power module
- Low distortion and high power-handling 12-inch woofers
- Recessed control panel
- Master Level control with Activity indicator (cabinet level adjustment)
- 3 Performance modes, Concert, Club and Monitor
- Defeatable 3 channel mixer with level controls and Clip indicators
- Bluetooth® input / streaming, not affected by Mixer Defeat



## TECHNICAL SPECIFICATIONS

Acoustical specifications	Frequency Response(-3db):	45Hz-16kHz
	Max SPL @ 1m:	118dB/124dB(PEAK)
	Dispersion (H x V):	80° × 120°
Transducers	Compression driver:	1 × 1" HF
	Woofer:	1 × 15" LF
Input/Output section		100 Hz HP with Sub, Mixer IN/OUT, Stereo/Mono out, 3.5mm Aux in, BT
	Input signal:	streaming
	Input Connectors:	2 x XLR, 2 x 1/4", 1/8", Bluetooth and Main in (XLR)
Processor section	Crossover frequencies:	1.6kHz
Power section	Total Power:	300W(RMS); 600W(MUSIC); 1200W(PEAK);
	Nominal Impedance (Ohm):	LF: 4Ω[]HF: 8Ω
	Cooling:	Speed controlled fan
	Power consumption(static):	19W
	Voltage range:	AC 110V/230V, 50Hz/60Hz
Physical specifications	Cabinet/Case Material:	Polypropylene Cabinet, ABS baffle, metal grille
	Handles:	2 × Plastic Handles(1 × Side / 1 × Back)
	Grille:	Powder Coated Steel with Grille Cloth
	Color:	Black
Size	Dimension (W x D x H):	433 x 374 x 685mm / (17 x 14.7 x 27in)
	Package Dimensions (W x D x H):	525 x 465 x 790mm / (20.7 x 18.3 x 31.1in)
Weight	Net Weight:	21.3 kg / 47 lb
	Gross Weight:	24 kg / 52.9 lb