β_3

DD406NF

Professional digital network power amplifier

DESCRIPTION



FEATURES

- Compact 1U body with a stable and ultra lightweight structure.
- 3.3 inch LCD display screen for more intuitive operation.
- Excellent sound quality, equipped with high-performance audio dedicated DSP.
- Supports Dante digital audio signal transmission.
- 4x4 audio routing matrix.
- Support importing and exporting 512 order FIR filter parameters per channel.
- Modular design, simple and easy to maintain, ensuring long-term reliable performance.
- Safe and controllable, power amplifier monitoring is achieved through a single network cable, allowing for quick local diagnosis.



TECHNICAL SPECIFICATIONS

RMS Stereo Power(8ohms):	4 x 650W
RMS Stereo Power(4ohms):	4 x 1100W
RMS Stereo Power(2ohms):	4 × 1870W
RMS Bridge Power(16ohms):	2 x 1300W
RMS Bridge Power(8ohms):	2 x 2200W
RMS Bridge Power(4ohms):	2 x 9520W
S/N Ratio:	72.1V
Frequency Response:	20Hz~20kHz (±2dB)
Power Supply Specifications:	90~260VAC,50/60Hz
Dimension (W x D x H):	483 x 45 x 370mm / (19 x 1.8 x 14.6in)
Net Weight:	9 kg / 19.8 lb