

SUB208

Dual 8" bandpass passive bass speaker

DESCRIPTION

The SUB subwoofer series adopts a brand new exterior structure and a new surface painting process to form a low-frequency speaker. The bass unit adopts a high-power voice coil with built-in high cut function. The high-power amplifier module without balanced network is designed without protection to minimize interference and improve sound quality. It can provide excellent low-frequency performance for applications such as mobile performances, churches, auditoriums, multifunctional halls, and small and medium-sized conference rooms. It can provide high sound pressure levels and has excellent performance in ultra-low frequency dynamic music.



FEATURES

- Ultra high output and excellent low-frequency performance
- Adopting a built-in low-frequency divider design, the sound quality is more natural, delicate, and pleasant to listen to.
- High power voice coil long stroke direct radiation low-frequency unit
- Exquisite, professional, and elegant appearance has perfect performance in any application situation
- Sturdy spray painted wooden box for long-lasting durability
- Sound quality characteristics: clean, powerful, and not losing elasticity.



TECHNICAL SPECIFICATIONS

Acoustical specifications	Frequency Response(-3db):	45Hz-200Hz
Transducers	Woofer:	2 x 8" Subwoofer
Input/Output section	Input Connectors:	Phoenix plug
	Sensitivity (1W @ 1m):	89dB
Power section	Total Power:	200W(RMS); 400W(MUSIC); 800W(PEAK);
	Nominal Impedance (Ohm):	4Ω
Physical specifications	Cabinet/Case Material:	15mm Plywood
	Grille:	Polypropylene plastic injection molding, power coated grill
	Color:	Black
Size	Dimension (W x D x H):	600 x 400 x 250mm / (23.6 x 15.7 x 9.8in)
	Package Dimensions (W x D x H):	505 x 355 x 725mm / (19.9 x 14 x 28.5in)
Weight	Net Weight:	17.9 kg / 39.5 lb
	Gross Weight:	21.5 kg / 47.4 lb