

MU401

4" Two Way Full Range Column Speaker

DESCRIPTION

MU401 installed column loudspeakers are used in applications including sound reinforcement for Houses of Worship, Events, Theme Parks, Transit Terminals and Shopping Malls etc. The MU series delivers extraordinary performance where highspeech intelligibility and natural sounding music is required at unmatched value.



FEATURES

- Frequency response(-3dB)100Hz-20kHz
- Sensitivity 87dB, Maximum SPL 100dB
- Dispersion(HxV) 90°x90°
- Rated Power 20W(RMS), 80W(Peak)
- Birch Plywood Construction
- Durable Polyurethane textured base paint
- Quick install U bracket included with multiple mounting points provided
- Designed for high speech intelligibility and naturalsounding music
- Optional MU401 hanging hardware

TECHNICAL SPECIFICATIONS

Acoustical specifications	Frequency Response(-3db):	160Hz-20kHz
	Max SPL @ 1m:	100dB/106dB(PEAK)
	Dispersion (H x V):	90° x 90°
Transducers	Compression driver:	1 x 25mm HF
	Woofer:	1 x 4" LF
Input/Output section	Input Connectors:	4-screw termina, 2 x XLR
	Sensitivity (1W @ 1m):	87dB
Processor section	Crossover frequencies:	3.8kHz
Power section	Total Power:	20W(RMS); 40W(MUSIC); 80W(PEAK);
	Nominal Impedance (Ohm):	8Ω
Physical specifications	Cabinet/Case Material:	15mm birch plywood
	Hardware:	6 x M8
	Grille:	White Polyurethane painting for cabinet & White Powder coated grille.
	Color:	White
Size	Dimension (W x D x H):	144 x 214 x 146mm / (5.7 x 8.4 x 5.7in)
	Package Dimensions (W x D x H):	195 x 276 x 195mm / (7.7 x 10.9 x 7.7in)
Weight	Net Weight:	3 kg / 6.6 lb
	Gross Weight:	4 kg / 8.8 lb