

# MU408

4" Two Way Full Range Column Speaker

## DESCRIPTION

MU408 installed line array column loudspeakers are used in applications including sound reinforcement for Houses of Worship, Events, Theme Parks, Transit Terminals and shopping malls etc. The T series delivers extraordinary performance where high speech intelligibility and natural sounding music is required at unmatched value.



## FEATURES

- Vertical line array of 8 x 4" LF driver
- 44mm compression driver loaded with wave guide
- Frequency response 80Hz-18kHz(-3dB)
- Sensitivity 92dB, Max SPL 116dB
- 150x 30 degree controlled coverage pattern
- Birch plywood construction
- Durable Polyurethane textured base paint
- Quick install U bracket included with multiple mounting points provided
- Designed for high speech intelligibility and natural sounding music
- Optional MU408 hanging hardware



TECHNICAL SPECIFICATIONS

Acoustical specifications	Frequency Response(-3db):	80Hz-18kHz
	Max SPL @ 1m:	116dB/122dB(PEAK)
	Dispersion (H x V):	150° x 30°
Transducers	Compression driver:	1 x 44mm HF
	Woofer:	8 x 4" LF
Input/Output section	Input Connectors:	4-screw termina, 2 x XLR
	Sensitivity (1W @ 1m):	92dB
Processor section	Crossover frequencies:	2kHz
Power section	Total Power:	240W(RMS); 480W(MUSIC); 960W(PEAK);
Physical specifications	Cabinet/Case Material:	15mm birch plywood
	Hardware:	6 x M8
	Grille:	White Polyurethane painting for cabinet & White Powder coated grille.
	Color:	White
Size	Dimension (W x D x H):	164 x 1138 x 233mm / (6.5 x 44.8 x 9.2in)
	Package Dimensions (W x D x H):	305 x 1240 x 243mm / (12 x 48.8 x 9.6in)
Weight	Net Weight:	16.7 kg / 36.8 lb
	Gross Weight:	18.2 kg / 40.1 lb