

MU401a

4" Two Way Full Range Active Column Speaker

DESCRIPTION

MU401a active installed column loudspeakers are used in applications including sound reinforcement for Houses of Worship, Events, Theme Parks, Transit Terminals and Shopping Malls etc. The MU series delivers extraordinary performance where highspeech intelligibility and natural sounding musicisrequired at unmatched value.



FEATURES

- Active speaker with 4" woofers and 1" tweete
- New generation Class-D amplification for MF /LF, Class-AB for HF
- Frequency response(-3dB) 100Hz-20kHz
- Sensitivity 87dB, Maximum SPL 100dB
- Dispersion(HxV)90°x90°
- Rated Power 50W(RMS)
- Birch Plywood Construction
- Durable Polyurethane textured base paint
- Quick install U bracket included with multiple mounting points provided
- Designed for high speech intelligibility and natural sounding music
- Optional MU401 a hanging hardware
- Dedicated STAND-BY switching mode for green energy saving

TECHNICAL SPECIFICATIONS

| | | |
|---------------------------|---------------------------------|---|
| Acoustical specifications | Frequency Response(-3db): | 160Hz-20kHz |
| | Max SPL @ 1m: | 100dB/106dB(PEAK) |
| | Dispersion (H x V): | 90° x 90° |
| Transducers | Compression driver: | 1 x 25mm HF |
| | Woofer: | 1 x 4" LF |
| Input/Output section | Input signal: | Balanced 20kΩ, Unbalanced 10kΩ |
| | Input Connectors: | 4-screw termina, 2 x XLR |
| Power section | Total Power: | 50W(RMS); 100W(MUSIC); 200W(PEAK); |
| | Voltage range: | AC 220V-240V~, 50/60Hz (or AC 110V-120V~, 50/60Hz) |
| Physical specifications | Cabinet/Case Material: | 15mm birch plywood |
| | Hardware: | 6 x M8 |
| | Grille: | White Polyurethane painting for cabinet & White Powder coated grille. |
| | Color: | White |
| Size | Dimension (W x D x H): | 144 x 214 x 146mm / (5.7 x 8.4 x 5.7in) |
| | Package Dimensions (W x D x H): | 195 x 276 x 195mm / (7.7 x 10.9 x 7.7in) |
| Weight | Net Weight: | 3 kg / 6.6 lb |
| | Gross Weight: | 4 kg / 8.8 lb |