

U15Ba

15" LF Active Speaker

DESCRIPTION

Portable and installed plastic loudspeakers used in applications including sound reinforcement in Front of House and Foldback applications in Houses of Worship, Events, Clubs, Rehearsal Halls etc. The U Active Series delivers extraordinary performance at unmatched value.



FEATURES

- High output SPL and sensitivity
- 1 x 15" high power low frequency transducer with 50mm voice coil
- Heavy duty protective grill
- Injection molded
- 2 x NL4 connector
- Cabinet design for FOH
- Suitable for use with any full range or mid/high speaker cabinets for extended low frequency, high quality music reproduction
- Integral 35mm pole receptacle for mounting full range or mid/high speaker cabinet

TECHNICAL SPECIFICATIONS

Acoustical specifications	Frequency Response(-3db):	80Hz-250Hz
	Max SPL @ 1m:	114dB/120dB(PEAK)
Transducers	Woofer:	1 x 15" LF
Input/Output section	Input signal:	Balanced 20kΩ, Unbalanced 10kΩ
	Input Connectors:	XLR K3P
Power section	Total Power:	400W(RMS); 800W(MUSIC); 1600W(PEAK);
	Nominal Impedance (Ohm):	4Ω
	Voltage range:	AC 220V-240V~, 50/60Hz (or AC 110V-120V~, 50/60Hz)
Physical specifications	Cabinet/Case Material:	Polypropylene injection moulding
	Hardware:	8 x M8 hanging point, SMART pole mount system
	Handles:	Two side, one rear
	Grille:	Powered coated grill
	Color:	Black
Size	Dimension (W x D x H):	485 x 460 x 700mm / (19.1 x 18.1 x 27.6in)
	Package Dimensions (W x D x H):	545 x 515 x 800mm / (21.5 x 20.3 x 31.5in)
Weight	Net Weight:	30.5 kg / 67.2 lb
	Gross Weight:	33.7 kg / 74.3 lb