S1200H 10" Mid/High Frequency Speaker



DESCRIPTION

Professional portable and installed plastic loudspeakers where high sound quality is required. Can be used in applications including sound reinforcement in Front of House and Foldback applications in Houses of Worship, Events, Clubs, Rehearsal Halls etc. The S Active Series is suitable for music and vocal reproduction in demanding applications.



FEATURES

- High output SPL and sensitivity
- 1 x 10" high power transducers
- 1 x 3" diaphragm compression driver
- 60° x 40° controlled coverage pattern
- 2 x NL4 connectors
- Injection molded
- Cabinet design for FOH use
- Suitable for use as a main system where a long throw is required
- Can augmented with sub speaker
- Portable system (stand), or permanent installation (wall, ceiling)
- Powder coated grill with foam backing
- Available in black or white



TECHNICAL SPECIFICATIONS

Acoustical specifications	Frequency Response(-3db):	400Hz-17kHz
	Max SPL @ 1m:	130dB/136dB(PEAK)
	Dispersion (H x V):	60° × 40°
Transducers	Compression driver:	1 x 3" HF
	Midrange:	1 × 10" MF
Input/Output section	Input Connectors:	2 x NL4
	Sensitivity (1W @ 1m):	105dB
Processor section	Crossover frequencies:	1.8kHz
Power section	Total Power:	300W(RMS); 600W(MUSIC); 1200W(PEAK);
	Nominal Impedance (Ohm):	Ω8
Physical specifications	Cabinet/Case Material:	Polypropylene Cabinet, ABS baffle, metal grille
	Handles:	1 × Plastic Handles
	Grille:	Powder Coated Steel with Grille Cloth
	Color:	Black
Size	Dimension (W x D x H):	416 x 423 x 721mm / (16.4 x 16.7 x 28.4in)
	Package Dimensions (W x D x H):	485 x 485 x 792mm / (19.1 x 19.1 x 31.2in)
Weight	Net Weight:	26.5 kg / 58.4 lb
	Gross Weight:	30.5 kg / 67.2 lb