

N15Ba

15" LF Active Plastic Speaker

DESCRIPTION

Portable and installed plastic loudspeakers used in applications including sound reinforcement in Front of House and Foldback applications in Houses of Worship, Events, Clubs, Rehearsal Halls etc. The N Active Series delivers extraordinary performance at unmatched value.



FEATURES

- High output SPL and sensitivity
- 1 x 15" high power low frequency transducer
- Heavy duty protective grill
- Injection molded
- Built-in power amplifier module
- Master volume control
- XLR input and output connectors
- Built in variable high cut filter
- Cabinet design for FOH
- Suitable for use with any full range or mid/high speaker cabinets for extended low frequency, high quality music reproduction
- Integral 35mm pole receptacle for mounting full range or mid/high speaker cabinet

TECHNICAL SPECIFICATIONS

Acoustical specifications	Frequency Response(-3db):	80Hz-250Hz
	Max SPL @ 1m:	120dB
Transducers	Woofer:	1 x 15" LF
Input/Output section	Input signal:	Balanced 20k Ω , Unbalanced 10k Ω
	Input Connectors:	2 x XLR
Power section	Total Power:	400W(RMS); 800W(MUSIC); 1600W(PEAK);
	Nominal Impedance (Ohm):	4 Ω
	Voltage range:	AC 220V-240V~, 50/60Hz (or AC 110V-120V~, 50/60Hz)
Physical specifications	Color:	Black
Size	Dimension (W x D x H):	485 x 460 x 700mm / (19.1 x 18.1 x 27.6in)
	Package Dimensions (W x D x H):	545 x 515 x 800mm / (21.5 x 20.3 x 31.5in)
Weight	Net Weight:	30.5 kg / 67.2 lb
	Gross Weight:	33.7 kg / 74.3 lb